



- ☐ 385 North Arrowhead Avenue - San Bernardino, CA 92415-0160 - (909) 884-4056
- ☐ 1647 East Holt Boulevard - Ontario, CA 91761 - (909) 458-9673
- ☐ 13911 Park Avenue, Suite 200 - Victorville, CA 92392 - (760) 243-3773
- ☐ San Bernardino County Vector Control Program  
2355 East 5th Street - San Bernardino, CA 92410-5201 - (909) 388-4600

JIM LINDLEY  
Interim Public Health Director

PAULA MEARES-CONRAD  
Interim Assistant Director of Public Health

MARGARET BEED  
Health Officer

DANIEL J. AVERA, REHS  
Chief of Environmental Health

Also serving the cities of

Adelanto	Montclair
Apple Valley	Needles
Barstow	Ontario
Big Bear Lake	Rancho Cucamonga
Chino	Redlands
Chino Hills	Rialto
Colton	San Bernardino
Fontana	Twentynine Palms
Grand Terrace	Upland
Hesperia	Victorville
Highland	Yucaipa
Loma Linda	Yucca Valley

## Acceptable Concrete Floor Sealers

The California Food Code requires that concrete floors must be sealed with a penetrating sealer which is nonabsorbant, grease and acid resistant, and designated by the manufacturer for use in food service areas. Sealers must be registered with the USDA, NSF, or approved by another Public Health Agency. *Floor paints and epoxy paints are not acceptable.*

The following represents a list of concrete sealers that meet the above requirements. This list is subject to review and revision at any time. DEHS does not endorse or promote any product or manufacturer. If a proposed sealer is not on this list, please submit specifications to Division of Environmental Health Services for review.

It is important that all sealers are applied as per the manufacturers' instructions, and be allowed to properly cure before use.

- Amercoat 335
- Aqua-Cure Vox
- Ashford Formula
- AZ Polymer Epoxy #600 (Two-part epoxy)
- Devoe Tru-Glaze WB 4406, 4408, 4030, 4418 (Two-part epoxy)
- Dural 356 (Two-part epoxy)
- Dur-A-Flex 'Shop-Floor' (Two-part epoxy)
- EpoxySystems' Products #222, 223, 226 (Two-part epoxies)
- Insl-X Aqua Tile/Insl-Tile (Two-part epoxy)
- Insl-X FREEZERKOTE [Designed for Coolers]
- L&M Seal Hard
- Pacific Polymer Res-Crete sealer H2O (Two-part epoxy)
- Pega-Cote 9200 (Two-part epoxy)
- Rust-oleum 6010 (Two-part epoxy)
- Select Epoxy-Kote WB-88 (Two-part epoxy)
- Sonneborn Kure-N-Harden
- Tech Guard Water Borne Epoxy (Two-part epoxy)
- Tnemec's StrataShield Enviro-Pox [Series 287]

Note: Sealers may need to be reapplied every six (6) months to remain effective.

March 2008

### Board of Supervisors

MARK H. UFFER  
County Administrative Officer

BRAD MITZELFELT ..... First District  
PAUL BIANE ..... Second District  
JOSIE GONZALES ..... Fifth District

DENNIS HANSBERGER ..... Third District  
GARY C. OVITT ..... Fourth District